



Amplifier card COB1808

The COB1808 board is a complete Class D audio amplifier in 2.0 with 25W+25W RMS. The kit includes 2 Bluetooth and Wi-Fi modules to receive the audio signal wirelessly from a foreign source, process it and output the audio file via the amplifier, but also relay it wirelessly to another identical module, working in cascade. Powered at 24VDC, it has the possibility of different settings via dip-switches and is equipped with two buttons for programming and initial settings.

| | |
|----------------------------|-------------------------|
| Board technology | Class D audio amplifier |
| Number of keys | 2 |
| Backlighting | No |
| Operation timer | Yes |
| BT / Wi-Fi Technology | Yes |
| Customisable functionality | Yes |
| Conformity | CE |

| | |
|-------------------------------|------------------------------|
| Input voltage | 24VDC |
| Display | No |
| Acoustic signaller | Yes |
| Remote control technology | Connections with smartphones |
| Plastic protection containers | No |
| Product size | 166x60 mm |

Field of application:

Audio system

Via Enrico Fermi 10 – Z.I. – 35020 LEGNARO (PD) – tel 049 790876 Fax 049 790993
C.F./P.IVA 00388610289
Numero REA 251745
cobofra@cobofra.com

-ELECTRONIC CONTROLS

-INVERTER

-CABLING

-LIGHTING SOLUTIONS

