



## Management board COB2204

The COB2204 board is designed for the management of electric motors for opening and closing skylights, industrial windows, and trapdoors in both directions of operation. Used for maximum 1100W asynchronous motors with cosfi 0.60, it has input fuse protection, direction management via the two relays and reverse protection.

|                           |           |
|---------------------------|-----------|
| Board technology          | Relays    |
| Output 1                  | Relay     |
| Output 3                  | /         |
| Micro contact 1           | /         |
| Thermal motor contact     | No        |
| Light signals             | No        |
| Serial 485                | No        |
| Remote control technology | No        |
| Operating temperature     | 0° - +60° |
| Conformity                | CE        |

|  |                |
|--|----------------|
| Input voltage                          | 230VAC 50-60Hz |
| Output 2                               | Relay          |
| Output 4                               | /              |
| Micro contact 2                        | /              |
| Electromechanical push-button controls | Yes            |
| Sensors                                | No             |
| Connecting electronic controls         | No             |
| BT/Wi-Fi Technology                    | No             |
| Product size                           | 78x50 mm       |

### Field of application:

Electric motors

Via Enrico Fermi 10 – Z.I. – 35020 LEGNARO (PD) – tel 049 790876 Fax 049 790993  
C.F./P.IVA 00388610289  
Numero REA 251745  
[cobofra@cobofra.com](mailto:cobofra@cobofra.com)

**-ELECTRONIC CONTROLS**

**-INVERTER**

**-CABLING**

**-LIGHTING SOLUTIONS**

